



WT 130 M,S1

TECHNICAL SPECIFICATIONS

NOT FOLDABLE

- Class of calculation H1B4
 - Lifting moment gross = 110634 lbfft
 - Lifting moment net = 89245 lbfft
 - Hydraulic outreach = 26,6 ft
 - First arm rigid type
 - Jib with one hydraulic extension with integrated fluid transmission system inside jib
 - Proportional flow control
 - Top seat laterally mounted controls with two additional functions at the jib extension
 - Stabilizers with hydraulic rotation 180°, extension and descent
 - Stabilizers ground bilateral controls
 - Ground hoisting control
 - Crane rotation 425° with double rack
 - Construction to Machinery Directives 2006/42/CE+UNI EN 12.999
 - Basic crane weight *: 4850 lb
- * The weight is indicative and referred to the basic crane without options or accessories, protection carters and ancillary equipments (grab, clamp, glass handling device)

OPTIONS

- Stabilizers with pantograph descent
- Proportional electro-hydraulic flow control with SCANRECO radio control
- Lateral top seat control with joystick and pedals
- Man standing platform with crane operative restricted area
- Glass container handling device
- Oil cooling system
- Top seat access ladder
- Working lights (top seat and jib light)
- Hour counter
- Dry seat foldable shelter