



# WT 130 M.S2

## TECHNICAL SPECIFICATIONS

### NOT FOLDABLE

- Class of calculation H1B4
  - Lifting moment gross = 88507 lbfft
  - Lifting moment net = 81131 lbfft
  - Hydraulic outreach = 31,66 ft
  - First arm rigid type
  - Jib with two hydraulic extensions with integrated fluid transmission system inside jib
  - Proportional flow control
  - Top seat laterally mounted controls with two additional functions at the jib extension
  - Stabilizers with hydraulic rotation 180°, extension and descent
  - Stabilizers ground bilateral controls
  - Ground hoisting control
  - Crane rotation 425° with double rack
  - Construction to Machinery Directives 2006/42/CE+UNI EN 12.999
  - Basic crane weight \*: 5180 lb
- \* The weight is indicative and referred to the basic crane without options or accessories, protection carters and ancillary equipments (grab, clamp, glass handling device)

### OPTIONS

- Stabilizers with pantograph descent
- Proportional electro-hydraulic flow control with SCANRECO radio control
- Lateral top seat control with joystick and pedals
- Man standing platform with crane operative restricted area
- Glass container handling device
- Oil cooling system
- Top seat access ladder
- Working lights (top seat and jib light)
- Hour counter
- Dry seat foldable shelter